

Interactive Flat Panel - Android 16 with EDLA and AI function				
Model		DT-866ST-3376	DT-8756ST-3376	DT-8866ST-3376
Display Parameter	Diagonal Size	65inch	75inch	86inch
	Effective Display Area	1428.48(H)*803.52(V)	1650.24(H)*928.26(V)	1895(H)*1096(V)
	Display Ratio	16:9	16:9	16:9
	Brightness	400cd/m²	400cd/m²	400cd/m²
	Contrast Ratio	1200:1	1200:1	1200:1
	Backlight Type	DLED	DLED	DLED
	Viewing Angle	178°(V)/178°(H)	178°(V)/178°(H)	178°(V)/178°(H)
	Resolution	3840 (H) X 2160 (V)	3840 (H) X 2160 (V)	3840(H) X 2160 (V)
	Audio Output Power	8Ω 15W*2 (20W*2 option)	8Ω 15W*2 (20W*2 option)	8Ω 15W*2 (20W*2 option)
	Built-in camera (option)			
	Built-in microphone (option)			
Touch	Touch technology	Infrared Multi Touch Technology	Infrared Multi Touch Technology	Infrared Multi Touch Technology
	Touch Points	40 points touch	40 points touch	40 points touch
	Drive	RED drive free	RED drive free	RED drive free
	Writing surface material	4mm tempered zero-bonding AG glass	4mm tempered zero-bonding AG glass	4mm tempered zero-bonding AG glass
	Touch Screen Sensor Mode	Finger, writing pen, hand with gloves or other non-transparent touch sensitive medium	Finger, writing pen, hand with gloves or other non-transparent touch sensitive medium	Finger, writing pen, hand with gloves or other non-transparent touch sensitive medium
	Resolution	32768X32768	32768X32768	32768X32768
	Communication Port	USB 2.0	USB 2.0	USB 2.0
	Min Recognition Dim	2mm	2mm	2mm
	Response Time	≤8ms	≤8ms	≤8ms
	Touch Accuracy	±1mm	±1mm	±1mm
	Anti-Interference	Incandescent lamp (220V, 100W), vertical distance 350mm above, The illumination intensity of the sun is up to 8000lx	Incandescent lamp (220V, 100W), vertical distance 350mm above, The illumination intensity of the sun is up to 8000lx	Incandescent lamp (220V, 100W), vertical distance 350mm above, The illumination intensity of the sun is up to 8000lx
	Calibration	Calibration free	Calibration free	Calibration free
	Touch Times	More than 60 million times in the same position	More than 60 million times in the same position	More than 60 million times in the same position
	Touch Power supply Mode	USB 5.0V power supply	USB 5.0V power supply	USB 5.0V power supply
Android Specs	Chipset	RK3576 (Android 16 with EDLA)	RK3576 (Android 16 with EDLA)	RK3576 (Android 16 with EDLA)
	CPU	A72 x4 + A53 x4, max 2.2Ghz	A72 x4 + A53 x4, max 2.2Ghz	A72 x4 + A53 x4, max 2.2Ghz
	GPU	G52 MC3	G52 MC3	G52 MC3
	Memory	16GB	16GB	16GB
	FLASH	256GB	256GB	256GB
	WiFi	wifi 6	wifi 6	wifi 6
	Bluetooth	5.4	5.4	5.4
Back port	Input	RS-232	1	1
		MIC IN	1	1
		RJ45	1	1
		HDMI 2.0	1	1
		Type-C (OTG)	1	1
	OUT	USB 3.0	1	1
		USB 2.0	2	2
		SPOF	1	1
		Earphone	1	1
		USB TOUCH	1	1
		HDMI OUT	1	1
Front port and function	USB 2.0	3	3	3
	HDMI 2.0	1	1	1
	USB TOUCH	1	1	1
	Type-C (full function)	1	1	1
	NFC (power on/off) (option)	1	1	1
	Pen Lifting Detection (option)	1	1	1
	Front keys (option)	Touch lock, Menu, Input, Annotation, Vocr, Vocr+, Power	1	1
Others	Power consumption	≤210W	≤250W	≤345W
	Standby consumption	≤0.5W	≤0.5W	≤0.5W
	Lifetime	60000 hours	60000 hours	60000 hours
	power supply	100-240V, 50/60Hz	100-240V, 50/60Hz	100-240V, 50/60Hz
	Demession	1465.2*903.4*103.5 (mm)	1707.6*1029*103.7 (mm)	1953.6*1168.4*103.7 (mm)
	VESA hole site	4-M8 hole site 500mm*400mm	4-M8 hole site 700mm*400mm	4-M8 hole site 800mm*500mm
	Net Weight	33.5KG	44.6KG	57KG
	Gross Weight	43.5KG	54.5KG	72.55KG
OPS (Purchase separately)	Interface	Conform to Intel® OPS-C JAE B0-pin connector	Conform to Intel® OPS-C JAE B0-pin connector	Conform to Intel® OPS-C JAE B0-pin connector
	National standard OPS size	L1384.6*W175.8*H42mm (42mm or 30mm)	L1384.6*W175.8*H42mm (42mm or 30mm)	L1384.6*W175.8*H42mm (42mm or 30mm)
	European standard OPS size	L1180*W119*H40mm	L1180*W119*H40mm	L1180*W119*H40mm
Accessories	Magnetic Whiteboard Pen X1pc, Wall-Mount Bracket X1set, Power Cord X1pc, Remote Control X1pc, WiFi antenna X2pcs			

